



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11336 - 6.5 Watt; MR16 LED; 2700K; GU5.3 base; 40 deg. Beam Angle; 12 Volt



ELECTRICAL

Technology:	LED
Watts:	6.5W
Volts:	12V
Lumens:	450L
CRI:	90+
Rg Value :	56
CCT (Kelvins):	2700K - Warm White
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable - Check the transformer/driver MFG for dimmer compatibility
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	50W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	950
Power Factor :	0.93
Light Source:	LED
CBCP :	950
Voltage Type:	AC/DC
Warranty:	5-Years

PACKAGING

Each UPC:	045923113369
Each Quantity:	1
Each Dimensions:	1.97 x 1.97 x 2.56

PHYSICAL

Base:	Bi Pin GU5.3
Shape:	MR16
Finish:	Gray
Lens Finish:	Gray
Lens Material:	Plastic (PS)
Dimensions (In.):	MOL: 1.772 - MOD: 1.969
Weight (Lbs.):	0.084
Material:	Metal / Plastic / Electronic Components
Housing Color:	Gray
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S11336 - 6.5 Watt; MR16 LED; 2700K; GU5.3 base; 40 deg. Beam Angle; 12 Volt

DIMMER COMPATIBILITY

Leviton	66ELV
---------	-------

Lutron	CTRP-253P
--------	-----------

Eaton	DALo6P-C2
-------	-----------

Leviton	DDMX1
---------	-------

Eaton	DULo6P-C2
-------	-----------

Lutron	DVRP-253P
--------	-----------

Leviton	DW6HD
---------	-------

Lutron	MA-PRO
--------	--------

Lutron	NTRP-250
--------	----------

Eaton	RF9640-ND
-------	-----------

Legrand	RH703PTUTC
---------	------------

Legrand	RHCL450PTC
---------	------------

Eaton	SUF7
-------	------

Eaton	VSULo6D
-------	---------