



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11340 - 6 Watt; MR16 LED; 2700K; GU5.3 base; 40 deg. Beam Angle; 24 Volt



ELECTRICAL

Technology:	LED
Watts:	6W
Volts:	24V
Lumens:	550L
CRI:	80+
CCT (Kelvins):	2700K - Warm White
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable - Check the transformer/driver MFG for dimmer compatibility
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase
Incandescent Equivalent :	50W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	1200
Power Factor :	0.92
Light Source:	LED
CBCP :	1200
Voltage Type:	AC/DC; Dual Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923113406
Each Quantity:	1
Each Dimensions:	1.97 x 1.97 x 2.56

PHYSICAL

Base:	Bi Pin GU5.3
Shape:	MR16
Finish:	Gray
Lens Finish:	Clear
Lens Material:	Plastic (PS)
Dimensions (In.):	MOL: 1.772 - MOD: 1.97
Weight (Lbs.):	0.084
Material:	Metal / Plastic / Electronic Components
Housing Color:	Gray
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S11340 - 6 Watt; MR16 LED; 2700K; GU5.3 base; 40 deg. Beam Angle; 24 Volt

DIMMER COMPATIBILITY

Lutron	CTRP-253P
Lutron	DVLV-600P
Lutron	MA-PRO
Lutron	NTRP-250
Lutron	SLV-600P