



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11355** - 8 Watt; A19 LED Filament; Clear; 3000K; Medium base; 120 Volt



### ELECTRICAL

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Technology:               | LED                                                |
| Watts:                    | 8W                                                 |
| Volts:                    | 120V                                               |
| Lumens:                   | 800L                                               |
| CRI:                      | 90+                                                |
| Rg Value :                | 57                                                 |
| CCT (Kelvins):            | 3000K - Warm White                                 |
| Beam Spread :             | 320                                                |
| Hours Rated:              | 15000                                              |
| Dimmable:                 | Yes-Dimmable -                                     |
| Dimmable Down To %:       | 100 to 10 percent                                  |
| Dimming Type :            | Forward Phase or Reverse Phase or Phase Selectable |
| Incandescent Equivalent : | 60W                                                |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                         |
| Operating Position:       | Universal                                          |
| Power Factor :            | 0.9                                                |
| Light Source:             | LED Filament                                       |
| Voltage Type:             | AC Only                                            |
| Warranty:                 | 2-Years                                            |

### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923113550       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 2.56 x 2.56 x 4.92 |

### INFO

|                  |                                             |
|------------------|---------------------------------------------|
| Additional Info: | S11355 (JA8/T24) for CA / S12415 (T20 only) |
|------------------|---------------------------------------------|

### PHYSICAL

|                   |                                         |
|-------------------|-----------------------------------------|
| Base:             | Medium                                  |
| Shape:            | A19                                     |
| Finish:           | Clear                                   |
| Lens Finish:      | Clear                                   |
| Lens Material:    | Plastic (PS)                            |
| Dimensions (In.): | MOL: 4.3 - MOD: 2.36                    |
| Weight (Lbs.):    | 0.08                                    |
| Material:         | Metal / Plastic / Electronic Components |
| Housing Color:    | None                                    |

### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| NOM Certificate No.:        | NTEC21ENM000307                   |
| NOM Expiration Date:        | 1/24/2023                         |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S11355** - 8 Watt; A19 LED Filament; Clear; 3000K; Medium base;  
120 Volt

#### DIMMER COMPATIBILITY

|         |             |
|---------|-------------|
| Leviton | 66ELV       |
| Satco   | 86/103      |
| Legrand | ADTP703TU   |
| Lutron  | AYCL-153P   |
| Lutron  | CTRP-253P   |
| Eaton   | DALo6P-C2   |
| Leviton | DDL06       |
| Leviton | DDMX1       |
| Leviton | DSL06-1LZ   |
| Lutron  | DVCL-153P   |
| Lutron  | DVRP-253P   |
| Leviton | DW6HD       |
| Leviton | IPE04-1L    |
| Leviton | IPL06       |
| Lutron  | LECL-153PH  |
| Lutron  | MA-PRO      |
| Lutron  | MACL-153M   |
| Lutron  | MSCL-OP153M |
| Lutron  | NTCL-250    |
| Lutron  | NTRP-250    |
| Lutron  | PD-10WX     |
| Lutron  | PD-6WCL     |
| Eaton   | RF9640-ND   |
| Legrand | RH703PTUTC  |
| Legrand | RHCL450PTC  |
| Lutron  | RRD-6CL     |

|       |         |
|-------|---------|
| Eaton | SALo6P  |
| Eaton | SUF7    |
| Eaton | VSULo6D |