



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11385 - 8 Watt C11 LED Filament; Clear; Candelabra base; 3000K; 90 CRI; 760 Lumens; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	8W
Volts:	120V
Lumens:	760L
CRI:	90+
R _g Value :	57
CCT (Kelvins):	3000K - Soft White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Operating Position:	Universal
Power Factor :	0.7
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923113857
Each Quantity:	1
Each Dimensions:	1.38 x 1.38 x 4.94

PHYSICAL

Base:	Candelabra
Shape:	C11
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 3.86 - MOD: 1.38
Weight (Lbs.):	0.03
Material:	Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S11385 - 8 Watt C11 LED Filament; Clear; Candelabra base; 3000K;
90 CRI; 760 Lumens; 120 Volt

DIMMER COMPATIBILITY

Leviton	6674
Leviton	66ELV
Satco	86/103
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DAL06P-C2
Leviton	DDL06
Leviton	DDMX1
Leviton	DSE06-10Z
Leviton	DSL06-1LZ
Leviton	DSM10
Eaton	DUL06P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	IPE04-1L
Leviton	IPL06
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX
Lutron	PD-6WCL
Lutron	RCL-153PNL

Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Eaton	SAL06P
Eaton	SUF7
Eaton	TAL06P-C2
Leviton	TSM10
Eaton	VSUL06D