



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11455 - 13 Watt A19 LED; 3000K; Dimmable; Medium base; 230 deg. Beam Angle; 4-pack



ELECTRICAL

Technology:	LED
Watts:	13W
Volts:	120V
Lumens:	1100L
CRI:	80+
CCT (Kelvins):	3000K - Soft White
Beam Spread :	230
Hours Rated:	15000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.84
Light Source:	LED
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923114557
Each Quantity:	1
Each Dimensions:	2.44 x 7.25 x 4.88

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Frost
Dimensions (In.):	MOL: 4.56 - MOD: 2.38
Weight (Lbs.):	0.49
Material:	Polycarbonate (PC) / High Heat Conductive Plastic Housing
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



S11455 - 13 Watt A19 LED; 3000K; Dimmable; Medium base; 230 deg. Beam Angle; 4-pack

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Satco	86/103
Lutron	AYCL-153P
Eaton	DALo6P-C2
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSL06
Leviton	DSL06-1LZ
Eaton	DULO6P-C2
Lutron	DVCL-153P
Leviton	DW6HD
Leviton	DZ6HD
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	PD-10WX
Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC

Leviton	RNLo6-10Z
Lutron	RRD-6CL
Satco	S11268
Eaton	SALo6P
Lutron	SCL-153P
Eaton	TALo6P-C2
Leviton	TSLo6
Eaton	VSULo6D