



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11554 - 5.5 Watt LED PL 2-PIN Dual Mode; 5000K; 550 Lumens; GX23 base; 50000 Average rated hours; 120 deg. Beam Angle; Type A/B Ballast Dependent or Ballast Bypass; 120-277 Volt



ELECTRICAL

Technology:	LED
Watts:	5.5W
Volts:	120V-277V
Lumens:	550L
CRI:	80+
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	13W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Ballast Type A/B/C :	Type A/B
Operating Position:	Universal
Power Factor :	0.97
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923115547
Each Quantity:	1
Each Dimensions:	1.34 x 0.94 x 6.14

PHYSICAL

Base:	GX23
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 5.98 - MOD: 1.26
Weight (Lbs.):	0.13
Material:	Glass / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21ENM000316
NOM Expiration Date:	1/24/2023
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S11554 - 5.5 Watt LED PL 2-PIN Dual Mode; 5000K; 550 Lumens; GX23 base; 50000 Average rated hours; 120 deg. Beam Angle; Type A/B Ballast Dependent or Ballast Bypass; 120-277 Volt

ACCESSORIES

	S8000	5 Watt LED Emergency Driver; 120-277 Volts
--	--------------	--

	S8002	10 Watt LED Emergency Driver; 120-277 Volt
--	--------------	--
