



Project/Job Name:

Location:

Fixture Type:

Notes:

**S11651** - 12 Watt 3 Foot T5 LED; CCT Selectable; G5 Base; Type B; Ballast Bypass; Single or Double Ended Wiring; White Finish; 120-277 Volt

- CCT Selectable



#### ELECTRICAL

Technology:	LED
Watts:	12W
Volts:	120V-277V
Lumens:	1500L/1575L/1600L/1650L/1550L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	160
Hours Rated:	50000
Incandescent Equivalent :	60W
Fluorescent Equivalent :	21W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	<25%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923116513
Each Quantity:	1
Each Dimensions:	33.46 x 0.87 x 0.87

#### PHYSICAL

Base:	Miniature Bi Pin
Shape:	T5
Finish:	White
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 33.98 - MOD: 0.88
Nominal Length:	36
Weight (Lbs.):	0.43
Material:	Plastic
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUs - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated
Tube Guard Use:	No



**S11651** - 12 Watt 3 Foot T5 LED; CCT Selectable; G5 Base; Type B;  
Ballast Bypass; Single or Double Ended Wiring; White Finish;  
120-277 Volt

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---