



Project/Job Name:

Location:

Fixture Type:

Notes:

S11652 - 13 Watt 4 Foot T5 LED; CCT Selectable; G5 Base; Type B; Ballast Bypass; Single or Double Ended Wiring; White Finish; 120-277 Volt

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	13W
Volts:	120V-277V
Lumens:	1700L/1775L/1800L/1850L/1750L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	160
Hours Rated:	50000
Incandescent Equivalent :	100W
Fluorescent Equivalent :	28W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	<25%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923116520
Each Quantity:	1
Each Dimensions:	45.28 x 0.87 x 0.87

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated
Tube Guard Use:	No



S11652 - 13 Watt 4 Foot T5 LED; CCT Selectable; G5 Base; Type B;
Ballast Bypass; Single or Double Ended Wiring; White Finish;
120-277 Volt

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
