



Project/Job Name:

Location:

Fixture Type:

Notes:

S11656 - 25 Watt 4 Foot T5 LED; CCT Selectable; G5 Base; Type B; Ballast Bypass; Double Ended Wiring; White Finish; 120-347 Volt

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	25W
Volts:	120V-347V
Lumens:	3000L/3450L/3500L/3600L/3400L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	160
Hours Rated:	50000
Incandescent Equivalent :	100W
Fluorescent Equivalent :	54W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	<25%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923116568
Each Quantity:	1
Each Dimensions:	45.28 x 0.87 x 0.87

PHYSICAL

Base:	Miniature Bi Pin
Shape:	T5
Finish:	White
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 45.8 - MOD: 0.88
Nominal Length:	48
Weight (Lbs.):	0.52
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUs - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-95JG10
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated
Tube Guard Use:	No



S11656 - 25 Watt 4 Foot T5 LED; CCT Selectable; G5 Base; Type B;
Ballast Bypass; Double Ended Wiring; White Finish; 120-347 Volt

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
