



Project/Job Name:

Location:

Fixture Type:

Notes:

S11731 - 17 Watt 48 Inch T8 LED; 35K/40K/50K CCT Selectable; Ballast Bypass with Battery Backup; G13 Base; 120-277 Volt

- CCT Selectable
- Has Driver
- Has Emergency Battery



PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 47.78 - MOD: 1.13
Nominal Length:	48
Weight (Lbs.):	1.13
Material:	Aluminum
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUs - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-MASCZT
BAA Compliant:	No
Enclosure Rating:	Not for use in fully enclosed vapor tight fixtures
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ELECTRICAL

Technology:	LED
Watts:	17W
Volts:	120V-277V
Lumens:	2100L/2300L/2200L
CRI:	80+
CCT (Kelvins):	35K/40K/50K - Neutral White to Natural Light
Beam Spread :	140
Hours Rated:	50000
Incandescent Equivalent :	90W
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended
THD:	<25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Battery Chemistry:	Lithium-ion (Li-ion)
Warranty:	5-Years

PACKAGING

Each UPC:	045923117312
Each Quantity:	1
Each Dimensions:	48.11 x 2.05 x 1.34

INFO

Additional Info:	5 Watts and 700 Lumens in Battery Backup Mode
Specification Note:	Height at switch: 1.30 Inches; Work time after power failure: 90 Minutes; Battery Recharge Time is 24 hours
Installation Note:	Not for use in vapor tight fixtures. Maximum Mounting Height: 13 Feet
Shatterproof Type:	Yes
Tube Guard Use:	No

