



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11743 - 9.5 Watt; 4 Foot; T8 LED; Medium bi-pin base; 5000K; 50000 Average rated hours; 1740 Lumens; Type A; Ballast dependent



ELECTRICAL

Technology:	LED
Watts:	9.5W
Volts:	Ballast Dependent
Lumens:	1740L
CRI:	80+
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Dimmable Down To %:	100 to 20 percent
Incandescent Equivalent :	75W
Fluorescent Equivalent :	32W/30W/28W/25W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Lamp Ballast Type A/B/C :	Type A
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Warranty:	5-Years

PACKAGING

Each UPC:	045923117435
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10

INFO

Specification Note:	Surge Protection
Installation Note:	Not for use in vapor tight fixtures.

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Gloss
Dimensions (In.):	MOL: 48 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.42
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PL2JWH754LKM
BAA Compliant:	No
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions