




Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____



S11744 - 14 Watt; 4Ft LED T8; 4000K; 347V Canada Only; G13 Base; Type B Ballast Bypass; Double Ended Wiring

- Flicker Free



ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	347V
Lumens:	1800L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	75W
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923117442
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Gloss White
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 47.78 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.43
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Additional Info:	CANADA ONLY
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 48.43 in. Width: 13.39 in. Height: 1.77 in.
Tube Guard Use:	Yes