



Project/Job Name:

Location:

Fixture Type:

Notes:

S11750 - 14 Watt T8 LED; Single Pin Base; CCT Selectable; PET Shatterproof Coated; White Finish; Type B; Ballast Bypass; 48 Inches; 120-277 Volt

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	120V-277V
Lumens:	1950L/2000L/1900L
CRI:	80+
CCT (Kelvins):	40K/50K/65K - Cool White to Daylight
Beam Spread :	180
Hours Rated:	50000
Incandescent Equivalent :	75W
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	<25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923117503
Each Quantity:	1
Each Dimensions:	48.00 x 1.00 x 1.00

PHYSICAL

Base:	Single Pin
Shape:	T8
Finish:	White
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 46 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.56
Material:	Glass / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUs - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated



S11750 - 14 Watt T8 LED; Single Pin Base; CCT Selectable; PET Shatterproof Coated; White Finish; Type B; Ballast Bypass; 48 Inches; 120-277 Volt

ACCESSORIES



80-984 T8 LED Support Clip; Center Mount Support; 2-Pack



S8002 10 Watt LED Emergency Driver; 120-277 Volt