



#### ELECTRICAL

Technology:	LED
Watts:	30W
Volts:	120V-277V
Lumens:	4200L/4300L/4100L
CRI:	80+
CCT (Kelvins):	40K/50K/65K - Cool White to Daylight
Beam Spread :	180
Hours Rated:	50000
Incandescent Equivalent :	125W
Fluorescent Equivalent :	87W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	<25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923117541
Each Quantity:	1
Each Dimensions:	72.00 x 1.00 x 1.00

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

Project/Job Name:

Location:

Fixture Type:

Notes:

**S11754** - 30 Watt T8 LED; Recessed Double Contact HO/VHO Base; CCT Selectable; Type B; Ballast Bypass; PET Shatterproof Coated; White Finish; 72 Inches; 120-277 Volt

- CCT Selectable



#### PHYSICAL

Base:	Recessed Double Contact HO/VHO
Shape:	T8
Finish:	White
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 70 - MOD: 1
Nominal Length:	72
Weight (Lbs.):	0.84
Material:	Glass / Plastic
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



**S11754** - 30 Watt T8 LED; Recessed Double Contact HO/VHO Base; CCT Selectable; Type B; Ballast Bypass; PET Shatterproof Coated; White Finish; 72 Inches; 120-277 Volt

## ACCESSORIES



**80-984** T8 LED Support Clip; Center Mount Support; 2-Pack



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt