



ELECTRICAL

| | |
|---------------------------|--------------------------------------|
| Technology: | LED |
| Watts: | 38W |
| Volts: | 120V-277V |
| Lumens: | 5400L/5500L/5300L |
| CRI: | 80+ |
| CCT (Kelvins): | 40K/50K/65K - Cool White to Daylight |
| Beam Spread : | 180 |
| Hours Rated: | 50000 |
| Incandescent Equivalent : | 150W |
| Fluorescent Equivalent : | 110W |
| Operating Temperature : | -20C (-4F) to +45C (+113F) |
| Ballasting Requirements : | Ballast Bypass |
| Lamp Ballast Type A/B/C : | Type B |
| Lamp End Type : | Double Ended |
| THD: | <25% |
| Power Factor : | 0.9 |
| Light Source: | LED |
| Voltage Type: | AC Only; Range Voltage |
| Warranty: | 5-Years |

PACKAGING

| | |
|------------------|---------------------|
| Each UPC: | 045923117558 |
| Each Quantity: | 1 |
| Each Dimensions: | 96.00 x 1.00 x 1.00 |

INFO

| | |
|--------------------|---|
| Installation Note: | Not for use in vapor tight fixtures. |
| Shatterproof Type: | PET Coated |
| Includes: | Each master case contains a 10 pack of item 80-984 (LED T8 Support Clip.) |

Project/Job Name:

Location:

Fixture Type:

Notes:

S11755 - 38 Watt T8 LED; Recessed Double Contact HO/VHO Base; CCT Selectable; Type B; Ballast Bypass; PET Shatterproof Coated; White Finish; 96 Inches; 120-277 Volt

- CCT Selectable



PHYSICAL

| | |
|-------------------|--------------------------------|
| Base: | Recessed Double Contact HO/VHO |
| Shape: | T8 |
| Finish: | White |
| Lens Finish: | Frost |
| Lens Material: | Glass |
| Dimensions (In.): | MOL: 93.88 - MOD: 1 |
| Nominal Length: | 96 |
| Weight (Lbs.): | 1.32 |
| Material: | Glass / Plastic |
| Housing Color: | White |

COMPLIANCE

| | |
|-----------------------------|---|
| Safety Listing: | cULus - Certified; cULus - Classified; cRUus - Recognized Component |
| Location Rating: | Damp |
| Indoor/Outoor: | Indoor |
| DLC Approved: | No |
| BAA Compliant: | No |
| Rated For Enclosed Fixture: | Yes |
| FCC Compliant: | Yes |
| IP Rating: | IP20 |
| NSF Approved: | Yes |
| RoHS Compliant: | Yes |
| Restrictions: | No Restrictions |



S11755 - 38 Watt T8 LED; Recessed Double Contact HO/VHO Base; CCT Selectable; Type B; Ballast Bypass; PET Shatterproof Coated; White Finish; 96 Inches; 120-277 Volt

ACCESSORIES



S8002

10 Watt LED Emergency Driver; 120-277 Volt
