



Project/Job Name:

Location:

Fixture Type:

Notes:

S11756 - 24/32/40 Wattage Selectable; 8 Foot T8 LED; 30/35/40/50/65K CCT Selectable; 120-277 Volt; FA8 Base

- Wattage Selectable

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	24W/32W/40W
Volts:	120V-277V
Lumens:	3500L/4400L/5500L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	100W
Fluorescent Equivalent :	40W/55W/70W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923117565
Each Quantity:	1
Each Dimensions:	48.39 x 6.50 x 7.44

INFO

Installation Note:	Not for use in vapor tight fixtures. Must use both sections; Provided support clips may differ from current PI Sheet (SN1394). Please refer to the Instruction Sheet provided in the master carton or downloaded from the website, https://www.satco.com/search/S11756
Min Compartment Size:	Length: 96.06 in. Width: 10.63 in. Height: 2.76 in.
Shatterproof Type:	PET Coated
Includes:	(20) R17d Base Adapters and (10) Fastening Clips included per case



S11756 - 24/32/40 Wattage Selectable; 8 Foot T8 LED;
30/35/40/50/65K CCT Selectable; 120-277 Volt; FA8 Base

ACCESSORIES



S8002

10 Watt LED Emergency Driver; 120-277 Volt
