

Project/Job Name:

Location:

Fixture Type:

Notes:



**S11764** - 9 Watt; 2 Foot LED; T8; CCT Selectable; Type B Ballast  
Bypass; G13 Base; 120-277 Volt

- CCT Selectable



#### ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V-277V
Lumens:	1150L/1150L/1250L/1250L/1250L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Warm White to Daylight
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	40W
Fluorescent Equivalent :	17W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	<25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923117640
Each Quantity:	1
Each Dimensions:	23.78 x 0.94 x 0.94

#### INFO

Additional Info:	Non CCT Selectable options are S39900-S39903
Installation Note:	Not for use in vapor tight fixtures.



**S11764** - 9 Watt; 2 Foot LED; T8; CCT Selectable; Type B Ballast  
Bypass; G13 Base; 120-277 Volt

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---