



Project/Job Name:

Location:

Fixture Type:

Notes:

S11766 - 14 Watt; 4 Foot LED; T8; CCT Selectable; Type B Ballast
Bypass; G13 Base; 120-277 Volt

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	120V-277V
Lumens:	1700L/1700L/1800L/1800L/1800L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Warm White to Daylight
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	75W
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	<25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923117664
Each Quantity:	1
Each Dimensions:	47.80 x 0.94 x 0.94

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	White
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 47.17 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.45
Material:	Glass / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUs - Recognized Component
Location Rating:	Damp
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-9MV7GT
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Additional Info:	Non CCT Selectable options are S39913-S39916
Installation Note:	Not for use in vapor tight fixtures.



S11766 - 14 Watt; 4 Foot LED; T8; CCT Selectable; Type B Ballast
Bypass; G13 Base; 120-277 Volt

ACCESSORIES



S8000

5 Watt LED Emergency Driver; 120-277 Volts
