



Project/Job Name:

Location:

Fixture Type:

Notes:

**S11900** - 2 Watt T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 150 Lumens; 120-277 Volt; Type B; Ballast Bypass; Double Ended Wiring



#### ELECTRICAL

Technology:	LED
Watts:	2W
Volts:	120V-277V
Lumens:	150L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	240
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	15W
Fluorescent Equivalent :	4W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Ballasting Requirements :	No ballast or external driver required
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923119002
Each Quantity:	1
Each Dimensions:	0.90 x 0.90 x 6.00

#### INFO

Additional Info:	Replaces F4T5/CW lamps; All glass tube
Installation Note:	Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring
Shatterproof Type:	PET Coated
ROI Category:	Internal-driver/Line Voltage (UL Type B) Lamps