



Project/Job Name:

Location:

Fixture Type:

Notes:

**S11901** - 2 Watt T5 LED; Miniature bi-pin base; 6500K; 50000 Average rated hours; 150 Lumens; 120-277 Volt; Type B; Ballast Bypass; Double Ended Wiring



#### ELECTRICAL

|                           |  |
|---------------------------|--|
| Technology:               | LED                                    |
| Watts:                    | 2W                                     |
| Volts:                    | 120V-277V                              |
| Lumens:                   | 150L                                   |
| CRI:                      | 80+                                    |
| CCT (Kelvins):            | 6500K - Daylight                       |
| Beam Spread :             | 240                                    |
| Hours Rated:              | 50000                                  |
| Dimmable:                 | Non-Dimmable -                         |
| Incandescent Equivalent : | 15W                                    |
| Fluorescent Equivalent :  | 4W                                     |
| Operating Temperature :   | -25C (-13F) to +45C (+113F)            |
| Ballasting Requirements : | No ballast or external driver required |
| Lamp Ballast Type A/B/C : | Type B                                 |
| Lamp End Type :           | Double Ended                           |
| THD:                      | 20%                                    |
| Power Factor :            | 0.9                                    |
| Light Source:             | LED                                    |
| Voltage Type:             | AC Only; Range Voltage                 |
| Warranty:                 | 5-Years                                |

#### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923119019       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 0.90 x 0.90 x 6.00 |

#### INFO

|                    |   |
|--------------------|---|
| Additional Info:   | Replaces F4T5/D lamps   |
| Installation Note: | Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring |
| Shatterproof Type: | PET Coated  |
| ROI Category:      | Internal-driver/Line Voltage (UL Type B) Lamps  |