



Project/Job Name: _____
Location: _____
Fixture Type: _____
Notes: _____

S11902 - 3 Watt T5 LED; Miniature bi-pin base; 4000K; 50000
Average rated hours; 270 Lumens; 120-277 Volt; Type B; Ballast
Bypass; Double Ended Wiring



ELECTRICAL

Technology:	LED
Watts:	3W
Volts:	120V-277V
Lumens:	270L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	240
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	25W
Fluorescent Equivalent :	6W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Ballasting Requirements :	No ballast or external driver required
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923119026
Each Quantity:	1
Each Dimensions:	0.90 x 0.90 x 9.00

INFO

Additional Info:	Replaces F6T5/CW lamps
Installation Note:	Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring
Shatterproof Type:	PET Coated
ROI Category:	Internal-driver/Line Voltage (UL Type B) Lamps

PHYSICAL

Base:	Miniature Bi Pin
Shape:	T5
Finish:	Frost
Lens Finish:	Frost
Dimensions (In.):	MOL: 8.91 - MOD: 0.83
Nominal Length:	9
Weight (Lbs.):	0.1
Material:	Glass

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21EL000412
NOM Expiration Date:	2/4/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions