



Project/Job Name:

Location:

Fixture Type:

Notes:

S11926 - 14 Watt T8 LED; Single pin base; 4000K; 50,000 Average rated hours; 1900 Lumens; Type B; 4 ft. Double Ended Bypass



ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	120V-277V
Lumens:	1900L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	75W
Fluorescent Equivalent :	32W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923119262
Each Quantity:	1
Each Dimensions:	48.00 x 1.00 x 1.00

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

PHYSICAL

Base:	Single Pin
Shape:	T8
Finish:	Frost
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 46 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.51
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEEL21007402-SOL
NOM Expiration Date:	12/29/2021
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S11926 - 14 Watt T8 LED; Single pin base; 4000K; 50,000 Average rated hours; 1900 Lumens; Type B; 4 ft. Double Ended Bypass

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
