



Project/Job Name:

Location:

Fixture Type:

Notes:

S11951 - 7 Watt; 18 Inch; T8 Linear LED; Medium Bi-Pin G13Base; 4000K; 50000 Average Rated Hours; 750 Lumens; Type B Ballast Bypass



ELECTRICAL

Technology:	LED
Watts:	7W
Volts:	120V-277V
Lumens:	750L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	160
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	75W
Fluorescent Equivalent :	15W
Operating Temperature :	-25C (-13F) to +40C (+104F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923119514
Each Quantity:	1
Each Dimensions:	18.00 x 1.10 x 1.10

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Frost
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 17.8 - MOD: 1.1
Nominal Length:	18
Weight (Lbs.):	0.19
Material:	Glass / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTE21CJTENo000079
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	ETL Sanitation listed (conforms to NSF)
RoHS Compliant:	Yes
Restrictions:	No Restrictions