



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11957 - 24 Watt; 8 Foot; T8 LED; Single pin base; 3500K; 50000 Average rated hours; 3200 Lumens; Type B; Ballast Bypass; Double Ended Wiring; DLC 5.1



ELECTRICAL

Technology:	LED
Watts:	24W
Volts:	120V-277V
Lumens:	3200L
CRI:	80+
CCT (Kelvins):	3500K - Neutral White
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	100W
Fluorescent Equivalent :	59W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923119576
Each Quantity:	1
Each Dimensions:	94.00 x 1.00 x 1.00

PHYSICAL

Base:	Single Pin
Shape:	T8
Finish:	White
Lens Finish:	White
Dimensions (In.):	MOL: 93.88 - MOD: 1
Nominal Length:	96
Weight (Lbs.):	0.88
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLH6WO8MgCE8
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Additional Info:	Suitable for Emergency Lighting only with Satco EM Driver #S8002
Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated



S11957 - 24 Watt; 8 Foot; T8 LED; Single pin base; 3500K; 50000
Average rated hours; 3200 Lumens; Type B; Ballast Bypass; Double
Ended Wiring; DLC 5.1

ACCESSORIES



S8002 10 Watt LED Emergency Driver; 120-277 Volt
