



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11959** - 24 Watt; 8 Foot; T8 LED; Single pin base; 5000K; 50000 Average rated hours; 3500 Lumens; Type B; Ballast Bypass; Double Ended Wiring; DLC 5.1



### ELECTRICAL

|                           |                            |
|---------------------------|----------------------------|
| Technology:               | LED                        |
| Watts:                    | 24W                        |
| Volts:                    | 120V-277V                  |
| Lumens:                   | 3500L                      |
| CRI:                      | 80+                        |
| CCT (Kelvins):            | 5000K - Natural Light      |
| Beam Spread :             | 210                        |
| Hours Rated:              | 50000                      |
| Incandescent Equivalent : | 100W                       |
| Fluorescent Equivalent :  | 59W                        |
| Operating Temperature :   | -20C (-4F) to +45C (+113F) |
| Ballasting Requirements : | Ballast Bypass             |
| Lamp Ballast Type A/B/C : | Type B                     |
| Lamp End Type :           | Double Ended               |
| THD:                      | 20%                        |
| Power Factor :            | 0.9                        |
| Light Source:             | LED                        |
| Voltage Type:             | AC Only; Range Voltage     |
| Warranty:                 | 5-Years                    |

### PACKAGING

|                  |                     |
|------------------|---------------------|
| Each UPC:        | 045923119590        |
| Each Quantity:   | 1                   |
| Each Dimensions: | 94.00 x 1.00 x 1.00 |

### PHYSICAL

|                   |                     |
|-------------------|---------------------|
| Base:             | Single Pin          |
| Shape:            | T8                  |
| Finish:           | White               |
| Lens Finish:      | White               |
| Dimensions (In.): | MOL: 93.88 - MOD: 1 |
| Nominal Length:   | 96                  |
| Weight (Lbs.):    | 0.88                |
| Material:         | Glass               |
| Housing Color:    | White               |

### COMPLIANCE

|                             |                                                                     |
|-----------------------------|---------------------------------------------------------------------|
| Safety Listing:             | cULus - Classified; cULus - Certified; cRUus - Recognized Component |
| Location Rating:            | Damp                                                                |
| Indoor/Outdoor:             | Indoor                                                              |
| DLC Approved:               | Yes                                                                 |
| DLC Classification:         | Standard                                                            |
| DLC ID:                     | PLD2OH5KIHQF                                                        |
| BAA Compliant:              | No                                                                  |
| Enclosure Rating:           | Enclosed Rated Lamp                                                 |
| Rated For Enclosed Fixture: | Yes                                                                 |
| FCC Compliant:              | Yes                                                                 |
| NSF Approved:               | Yes                                                                 |
| RoHS Compliant:             | Yes                                                                 |
| Restrictions:               | No Restrictions                                                     |

### INFO

|                    |                                                                  |
|--------------------|------------------------------------------------------------------|
| Additional Info:   | Suitable for Emergency Lighting only with Satco EM Driver #S8002 |
| Installation Note: | Not for use in vapor tight fixtures.                             |
| Shatterproof Type: | PET Coated                                                       |



**S11959** - 24 Watt; 8 Foot; T8 LED; Single pin base; 5000K; 50000  
Average rated hours; 3500 Lumens; Type B; Ballast Bypass; Double  
Ended Wiring; DLC 5.1

## ACCESSORIES

---



**S8002**

10 Watt LED Emergency Driver; 120-277 Volt

---