



Project/Job Name:

Location:

Fixture Type:

Notes:

S11965 - 18 Watt T8 LED; 4 Foot; 6500K; Recessed Double Contact base; 50000 Average rated hours; 2500 Lumens; Type B; Ballast Bypass; Double Ended Wiring



ELECTRICAL

Technology:	LED
Watts:	18W
Volts:	120V-277V
Lumens:	2500L
CRI:	80+
CCT (Kelvins):	6500K - Daylight
Beam Spread :	160
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	90W
Fluorescent Equivalent :	63W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923119651
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10

PHYSICAL

Base:	Recessed Double Contact HO/VHO
Shape:	T8
Finish:	White
Lens Finish:	White
Lens Material:	Glass
Dimensions (In.):	MOL: 46 - MOD: 1.1
Nominal Length:	48
Weight (Lbs.):	0.58
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTE21CJTENo000079
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
B.U.G Rating:	Bo-Uo-Go
Restrictions:	No Restrictions

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated
Tube Guard Use:	Yes



S11965 - 18 Watt T8 LED; 4 Foot; 6500K; Recessed Double Contact base; 50000 Average rated hours; 2500 Lumens; Type B; Ballast Bypass; Double Ended Wiring

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
