



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11976 - 12 Watt; 48 Inch; T8 LED; G13 base; Dual Mode Hybrid
Type A/B; 4000K; 1800 Lumens



ELECTRICAL

Technology:	LED
Watts:	12W
Volts:	120V-277V
Lumens:	1800L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	50W
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Ballast Type A/B/C :	Type A/B
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923119767
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Frost
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 48 - MOD: 1
Nominal Length:	48
Weight (Lbs.):	0.48
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-BZNC87
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 47.83 in. Width: 23.82 in. Height: 2.95 in.



S11976 - 12 Watt; 48 Inch; T8 LED; G13 base; Dual Mode Hybrid
Type A/B; 4000K; 1800 Lumens

ACCESSORIES

	S8000	5 Watt LED Emergency Driver; 120-277 Volts
--	--------------	--

	S8002	10 Watt LED Emergency Driver; 120-277 Volt
--	--------------	--
