



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12116 - 4.5 Watt; B11 LED Filament; Clear; 350 Lumens; 4000K;
European base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	4.5W
Volts:	120V
Lumens:	350L
CRI:	80+
Rg Value :	13
CCT (Kelvins):	4000K - Cool White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Operating Position:	Universal
Power Factor :	0.7
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923121166
Each Quantity:	1
Each Dimensions:	1.39 x 1.39 x 3.94

PHYSICAL

Base:	European Intermediate
Shape:	B11
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 3.88 - MOD: 1.38
Weight (Lbs.):	0.04
Material:	Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cRUus
Location Rating:	Wet
DLC Approved:	No
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S12116 - 4.5 Watt; B11 LED Filament; Clear; 350 Lumens; 4000K;
European base; 120 Volt

DIMMER COMPATIBILITY

Lutron	AYCL-153P
--------	-----------

Lutron	CTRP-253P
--------	-----------

Leviton	DDMX1
---------	-------

Eaton	Dulo6P-C2
-------	-----------

Lutron	DVCL-153P
--------	-----------

Lutron	DVRP-253P
--------	-----------

Leviton	DW6HD
---------	-------

Lutron	LECL-153PH
--------	------------

Lutron	MA-PRO
--------	--------

Lutron	MACL-153M
--------	-----------

Lutron	MSCL-OP153M
--------	-------------

Lutron	NTCL-250
--------	----------

Lutron	NTRP-250
--------	----------

Lutron	PD-10WX
--------	---------

Lutron	PD-6WCL
--------	---------

Eaton	RF9640-ND
-------	-----------

Legrand	RH703PTUTC
---------	------------

Legrand	RHCL450PTC
---------	------------

Lutron	RRD-6CL
--------	---------

Satco	S11268
-------	--------

Eaton	SALo6P
-------	--------

Eaton	SUF7
-------	------

Eaton	VSULo6D
-------	---------