



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S12130** - 5 Watt Mini LED; G9 Base; 3000K; Clear Finish; 120 Volt



#### ELECTRICAL

|                           |                                                                |
|---------------------------|----------------------------------------------------------------|
| Technology:               | LED                                                            |
| Watts:                    | 5W                                                             |
| Volts:                    | 120V                                                           |
| Lumens:                   | 550L                                                           |
| CRI:                      | 80+                                                            |
| CCT (Kelvins):            | 3000K - Soft White                                             |
| Beam Spread :             | 300                                                            |
| Hours Rated:              | 25000                                                          |
| Dimmable:                 | Yes-Dimmable - 120V only                                       |
| Dimmable Down To %:       | 100 to 10 percent                                              |
| Dimming Type :            | Forward Phase or Reverse Phase<br>or Phase Selectable or Triac |
| Incandescent Equivalent : | 40W                                                            |
| Operating Temperature :   | -20C (-4F) to +40C (+104F)                                     |
| Power Factor :            | 0.9                                                            |
| Light Source:             | LED                                                            |
| Voltage Type:             | AC Only                                                        |
| Warranty:                 | 5-Years                                                        |

#### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923121302       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 3.27 x 0.75 x 4.84 |

#### INFO

|                    |                                                              |
|--------------------|--------------------------------------------------------------|
| Additional Info:   | Housing Material: Ceramic; Lens Material: Polycarbonate (PC) |
| Installation Note: | Not for use in vapor tight fixtures.                         |

#### PHYSICAL

|                   |                              |
|-------------------|------------------------------|
| Base:             | G9 Double Loop               |
| Shape:            | T4                           |
| Finish:           | Clear                        |
| Dimensions (In.): | MOL: 2.17 - MOD: 0.75        |
| Weight (Lbs.):    | 0.06                         |
| Material:         | Ceramic / Polycarbonate (PC) |
| Housing Color:    | White                        |

#### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| Indoor/Outdoor:             | Indoor                            |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S12130** - 5 Watt Mini LED; G9 Base; 3000K; Clear Finish; 120 Volt

#### DIMMER COMPATIBILITY

|         |           |
|---------|-----------|
| Leviton | 66ELV     |
| Satco   | 80/2699   |
| Satco   | 80/2700   |
| Satco   | 80/2701   |
| Satco   | 80/2702   |
| Satco   | 80/2703   |
| Satco   | 80/2704   |
| Satco   | 86/103    |
| Lutron  | AYCL-153P |
| Lutron  | AYCL-253P |
| Lutron  | CTCL-153P |
| Lutron  | CTRP-253P |
| Eaton   | DALo6P-C2 |
| Leviton | DDLo6     |
| Leviton | DDMX1     |
| Leviton | DG6HD     |
| Leviton | DH6HD     |
| Leviton | DL6HD     |
| Leviton | DSEo6-10Z |
| Leviton | DSL06     |
| Leviton | DSM10     |
| Lutron  | DVCL-153P |
| Lutron  | DVCL-253P |
| Lutron  | DVRP-253P |
| Leviton | DW6HD     |
| Leviton | DZ6HD     |

|                  |             |
|------------------|-------------|
| <b>Lutron</b>    | HQR-3LD     |
| <b>Lutron</b>    | HQR-3PD     |
| <b>Lutron</b>    | HQRA-PRO    |
| <b>Lutron</b>    | HQRD-10D    |
| <b>Lutron</b>    | HQRD-10NBD  |
| <b>Lutron</b>    | HQRD-6CL    |
| <b>Lutron</b>    | HQRD-6ND    |
| <b>Lutron</b>    | HQRD-HN6BRL |
| <b>Lutron</b>    | HQRD-PRO    |
| <b>Lutron</b>    | HRST-PRO-N  |
| <b>Leviton</b>   | IPE04-1L    |
| <b>Lutron</b>    | LECL-153P   |
| <b>Lutron</b>    | MA-PRO      |
| <b>Lutron</b>    | MACL-153M   |
| <b>Lutron</b>    | MACL-LFQ    |
| <b>Lutron</b>    | MAELV-600   |
| <b>Precision</b> | MR42400PLS  |
| <b>Lutron</b>    | MRF2-3LD    |
| <b>Lutron</b>    | MRF2-3PD    |
| <b>Lutron</b>    | MSCL-OP153M |
| <b>Lutron</b>    | NTCL-250    |
| <b>Lutron</b>    | NTRP-250    |
| <b>Hubbell</b>   | NXFRD-UNV   |
| <b>Overdrive</b> | ODMR0205    |
| <b>Lutron</b>    | PD-10NXD    |
| <b>Lutron</b>    | PD-3PCL     |
| <b>Lutron</b>    | PD-5NE      |
| <b>Lutron</b>    | PD-6WCL     |

|                |              |
|----------------|--------------|
| <b>Lutron</b>  | PHPM-WBX-120 |
| <b>Lutron</b>  | RCL-153PNL   |
| <b>Leviton</b> | REL06-W/W    |
| <b>Eaton</b>   | RF9640-ND    |
| <b>Legrand</b> | RHCL450PTC   |
| <b>Leviton</b> | RNL06-10Z    |
| <b>Lutron</b>  | RRD-10D      |
| <b>Lutron</b>  | RRD-3LD      |
| <b>Lutron</b>  | RRD-3PD      |
| <b>Lutron</b>  | RRD-6CL      |
| <b>Lutron</b>  | RRD-6ND      |
| <b>Lutron</b>  | RRD-H6BRL    |
| <b>Lutron</b>  | RRD-PRO      |
| <b>Lutron</b>  | RRST-PRO-N   |
| <b>Satco</b>   | S11268       |
| <b>Satco</b>   | S11270       |
| <b>Eaton</b>   | SAL06P       |
| <b>Lutron</b>  | SCL-153P     |
| <b>Lutron</b>  | SELV-300P    |
| <b>Lutron</b>  | SLV-600P     |
| <b>Lutron</b>  | ST-PRO-N     |
| <b>Lutron</b>  | STCL-153M    |
| <b>Eaton</b>   | SUF7         |
| <b>Eaton</b>   | TAL06P-C2    |
| <b>Lutron</b>  | TGCL-153PH   |
| <b>Leviton</b> | TSM10        |
| <b>Lutron</b>  | TTCL-100H    |
| <b>Leviton</b> | VPE06-1LZ    |

|         |            |
|---------|------------|
| Eaton   | VSULo6D    |
| Acuity  | WSX-PDT-WH |
| Legrand | WWRL5oWH   |