



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12326 - 6.5 Watt T6 LED; Clear Finish; G8 Base; 3000K; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	6.5W
Volts:	120V
Lumens:	650L
CRI:	80+
CCT (Kelvins):	3000K - Soft White
Beam Spread :	300
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Triac
Incandescent Equivalent :	50W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923123269
Each Quantity:	1
Each Dimensions:	1.50 x 1.50 x 2.95

INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------

PHYSICAL

Base:	Bi Pin G8
Shape:	T6
Finish:	Clear
Dimensions (In.):	MOL: 2.52 - MOD: 0.75
Weight (Lbs.):	0.06
Material:	Ceramic / Polycarbonate (PC)
Housing Color:	Clear

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

Satco	80/2699
Satco	80/2700
Satco	80/2701
Satco	80/2702
Satco	80/2703
Satco	80/2704
Lutron	AYCL-153P
Lutron	AYCL-253P
Lutron	CTCL-153P
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Eaton	DULo6P-C2
Lutron	DVCL-153P
Lutron	DVCL-253P
Leviton	DW6HD
Leviton	DZ6HD
Lutron	HQR-3LD
Lutron	HQR-3PD
Lutron	HQRD-10D
Lutron	HQRD-10NBD
Lutron	HQRD-6CL
Lutron	HQRD-6ND
Lutron	HQRD-HN6BRL

Lutron LECL-153P

Lutron	MACL-153M
Lutron	MACL-LFQ
Lutron	MRF2-3LD
Lutron	MRF2-3PD
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	PD-10NXD
Lutron	PD-3PCL
Lutron	PD-6WCL
Lutron	RCL-153PNL
Legrand	RHCL450PTC
Lutron	RRD-10D
Lutron	RRD-3LD
Lutron	RRD-3PD
Lutron	RRD-6ND
Lutron	RRD-H6BRL
Satco	S11270
Lutron	SCL-153P
Lutron	STCL-153M
Lutron	TGCL-153PH
Eaton	VSUL06D
Acuity	WSX-PDT-WH