



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S12339** - 6.5 Watt T6 LED; Clear Finish; E11 Base; 5000K; 120 Volt



### ELECTRICAL

|                           |                                                                |
|---------------------------|----------------------------------------------------------------|
| Technology:               | LED                                                            |
| Watts:                    | 6.5W                                                           |
| Volts:                    | 120V                                                           |
| Lumens:                   | 650L                                                           |
| CRI:                      | 80+                                                            |
| CCT (Kelvins):            | 5000K - Natural Light                                          |
| Beam Spread :             | 300                                                            |
| Hours Rated:              | 25000                                                          |
| Dimmable:                 | Yes-Dimmable - 120V only                                       |
| Dimmable Down To %:       | 100 to 10 percent                                              |
| Dimming Type :            | Forward Phase or Reverse Phase<br>or Phase Selectable or Triac |
| Incandescent Equivalent : | 50W                                                            |
| Operating Temperature :   | -20C (-4F) to +40C (+104F)                                     |
| Power Factor :            | 0.9                                                            |
| Light Source:             | LED                                                            |
| Voltage Type:             | AC Only                                                        |
| Warranty:                 | 5-Years                                                        |

### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923123399       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 1.50 x 1.50 x 2.95 |

### INFO

|                    |                                      |
|--------------------|--------------------------------------|
| Installation Note: | Not for use in vapor tight fixtures. |
|--------------------|--------------------------------------|

### PHYSICAL

|                   |                              |
|-------------------|------------------------------|
| Base:             | Mini Candelabra              |
| Shape:            | T6                           |
| Finish:           | Clear                        |
| Dimensions (In.): | MOL: 2.83 - MOD: 0.75        |
| Weight (Lbs.):    | 0.06                         |
| Material:         | Ceramic / Polycarbonate (PC) |
| Housing Color:    | White                        |

### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| Indoor/Outdoor:             | Indoor                            |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S12339** - 6.5 Watt T6 LED; Clear Finish; E11 Base; 5000K; 120 Volt

#### DIMMER COMPATIBILITY

|         |             |
|---------|-------------|
| Satco   | 80/2699     |
| Satco   | 80/2700     |
| Satco   | 80/2701     |
| Satco   | 80/2702     |
| Satco   | 80/2703     |
| Satco   | 80/2704     |
| Lutron  | AYCL-153P   |
| Lutron  | AYCL-253P   |
| Lutron  | CTCL-153P   |
| Leviton | DDMX1       |
| Leviton | DG6HD       |
| Leviton | DH6HD       |
| Leviton | DL6HD       |
| Eaton   | DULo6P-C2   |
| Lutron  | DVCL-153P   |
| Lutron  | DVCL-253P   |
| Leviton | DW6HD       |
| Leviton | DZ6HD       |
| Lutron  | HQR-3LD     |
| Lutron  | HQR-3PD     |
| Lutron  | HQRD-10D    |
| Lutron  | HQRD-10NBD  |
| Lutron  | HQRD-6CL    |
| Lutron  | HQRD-6ND    |
| Lutron  | HQRD-HN6BRL |

|        |           |
|--------|-----------|
| Lutron | LECL-153P |
|--------|-----------|

SATCO.COM | 800-437-2826

© Satco Products, Inc.  
All rights reserved 2026

|                |             |
|----------------|-------------|
| <b>Lutron</b>  | MACL-153M   |
| <b>Lutron</b>  | MACL-LFQ    |
| <b>Lutron</b>  | MRF2-3LD    |
| <b>Lutron</b>  | MRF2-3PD    |
| <b>Lutron</b>  | MSCL-OP153M |
| <b>Lutron</b>  | NTCL-250    |
| <b>Lutron</b>  | PD-10NXD    |
| <b>Lutron</b>  | PD-3PCL     |
| <b>Lutron</b>  | PD-6WCL     |
| <b>Lutron</b>  | RCL-153PNL  |
| <b>Legrand</b> | RHCL450PTC  |
| <b>Lutron</b>  | RRD-10D     |
| <b>Lutron</b>  | RRD-3LD     |
| <b>Lutron</b>  | RRD-3PD     |
| <b>Lutron</b>  | RRD-6ND     |
| <b>Lutron</b>  | RRD-H6BRL   |
| <b>Satco</b>   | S11270      |
| <b>Lutron</b>  | SCL-153P    |
| <b>Lutron</b>  | STCL-153M   |
| <b>Lutron</b>  | TGCL-153PH  |
| <b>Eaton</b>   | VSUL06D     |
| <b>Acuity</b>  | WSX-PDT-WH  |