



Project/Job Name:

Location:

Fixture Type:

Notes:

**S12401** - 5 Watt A15 LED Filament; Clear; Medium Base; 3000K; 90 CRI; 120 Volt



### ELECTRICAL

|                           |                                                       |
|---------------------------|-------------------------------------------------------|
| Technology:               | LED                                                   |
| Watts:                    | 5W                                                    |
| Volts:                    | 120V                                                  |
| Lumens:                   | 450L                                                  |
| CRI:                      | 90+                                                   |
| Rg Value :                | 43                                                    |
| CCT (Kelvins):            | 3000K - Soft White                                    |
| Beam Spread :             | 320                                                   |
| Hours Rated:              | 15000                                                 |
| Dimmable:                 | Yes-Dimmable -                                        |
| Dimmable Down To %:       | 100 to 20 percent                                     |
| Dimming Type :            | Forward Phase or Reverse Phase<br>or Phase Selectable |
| Incandescent Equivalent : | 40W                                                   |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                            |
| Candlepower :             | 40                                                    |
| Power Factor :            | 0.7                                                   |
| Light Source:             | LED Filament                                          |
| Voltage Type:             | AC Only                                               |
| Warranty:                 | 2-Years                                               |

### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923124013       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 2.05 x 2.05 x 3.94 |

### PHYSICAL

|                   |                       |
|-------------------|-----------------------|
| Base:             | Medium                |
| Shape:            | A15                   |
| Finish:           | Clear                 |
| Dimensions (In.): | MOL: 3.39 - MOD: 1.89 |
| Weight (Lbs.):    | 0.05                  |
| Material:         | Aluminum / Glass      |
| Housing Color:    | None                  |

### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Wet                               |
| Indoor/Outdoor:             | Indoor; Outdoor                   |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| NOM Certificate No.:        | NTEC21ENM001771                   |
| NOM Expiration Date:        | 1/28/2023                         |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S12401** - 5 Watt A15 LED Filament; Clear; Medium Base; 3000K; 90 CRI; 120 Volt

DIMMER COMPATIBILITY

|         |            |
|---------|------------|
| Leviton | 6674       |
| Lutron  | AYCL-153P  |
| Lutron  | CTCL-153P  |
| Lutron  | CTRP-253P  |
| Lutron  | DVCL-153P  |
| Lutron  | DVRP-253P  |
| Lutron  | LECL-153PH |
| Lutron  | MA-PRO     |
| Lutron  | MACL-153M  |
| Lutron  | NTCL-250   |
| Lutron  | NTRP-250   |
| Lutron  | PD-6WCL    |
| Satco   | S11268     |
| Lutron  | SCL-153P   |
| Eaton   | SUF7       |
| Leviton | TSM10      |