



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12417 - 8 Watt A19 LED Filament; Clear; Medium Base; 4000K; 90 CRI; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	8W
Volts:	120V
Lumens:	800L
CRI:	90+
Rg Value :	49
CCT (Kelvins):	4000K - Cool White
Beam Spread :	320
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	60W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Candlepower :	60
Power Factor :	0.7
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923124174
Each Quantity:	1
Each Dimensions:	2.52 x 2.52 x 4.57

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Clear
Dimensions (In.):	MOL: 4.02 - MOD: 2.36
Weight (Lbs.):	0.06
Material:	Aluminum / Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21EN001640
NOM Expiration Date:	4/12/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S12417 - 8 Watt A19 LED Filament; Clear; Medium Base; 4000K; 90 CRI; 120 Volt

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Lutron	AYCL-153P
Lutron	CTCL-153P
Lutron	CTRP-253P
Eaton	DALo6P-C2
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSEo6-10Z
Leviton	DSM10
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	DZ6HD
Leviton	IPLo6
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MRF2-6CL
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	RRD-PRO

Lutron	SCL-153P
Eaton	SUF7
Leviton	TSM10