



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S12460 - 5 Watt A19 LED Filament; Clear; 2700K; Medium Base;
120 Volt; 4-Pack



ELECTRICAL

Technology:	LED
Watts:	5W
Volts:	120V
Lumens:	450L
CRI:	90+
Rg Value :	52
CCT (Kelvins):	2700K - Warm White
Beam Spread :	280
Hours Rated:	15000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.7
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923124600
Each Quantity:	1
Each Dimensions:	10.24 x 2.56 x 4.72

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Clear
Dimensions (In.):	MOL: 4.33 - MOD: 2.36
Weight (Lbs.):	0.07
Material:	Glass
Housing Color:	Clear

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S12460 - 5 Watt A19 LED Filament; Clear; 2700K; Medium Base;
120 Volt; 4-Pack

DIMMER COMPATIBILITY

LEVITON	6672
LUTRON	AYCL-153P
LUTRON	AYCL-253P
LUTRON	CTCL-153P
LUTRON	CTRP-253P
LEVITON	DDMX1
LEVITON	DG6HD
LEVITON	DH6HD
LEVITON	DL6HD
LEVITON	DSL06
LEVITON	DSL06-1LZ
LUTRON	DVCL-153P
LUTRON	DVCL-253P
LUTRON	DVRP-253P
LEVITON	DZ6HD
LUTRON	HQRA-PRO
LUTRON	HQRD-10D
LUTRON	HQRD-10NBD
LUTRON	HQRD-6ND
LUTRON	HQRD-HN6BRL
LUTRON	HQRD-PRO
LUTRON	HRST-PRO-N
LUTRON	LECL-153P
LUTRON	MA-PRO
LUTRON	MACL-LFQ
LUTRON	MRF2S-6ELV

LUTRON	NTCL-250
LUTRON	PD-10NXD
LUTRON	RCL-153PNL
LEVITON	RNL06-10Z
LUTRON	RRD-10D
LUTRON	RRD-6ND
LUTRON	RRD-H6BRL
LUTRON	RRD-PRO
LUTRON	RRST-PRO-N
SATCO	S11268
LUTRON	SCL-153P
LUTRON	ST-PRO-N
LUTRON	STCL-153M
Eaton	SUF7
LUTRON	TGCL-153PH
LEVITON	TSL06
LEVITON	TSM10
LUTRON	TTCL-100H