



#### ELECTRICAL

|                           |                             |
|---------------------------|-----------------------------|
| Technology:               | LED                         |
| Watts:                    | 60W                         |
| Volts:                    | 120V-277V                   |
| Lumens:                   | 5880L                       |
| CRI:                      | 80+                         |
| Rg Value :                | 8                           |
| CCT (Kelvins):            | 4000K - Cool White          |
| Beam Spread :             | 120-270                     |
| Hours Rated:              | 50000                       |
| Dimmable:                 | Non-Dimmable -              |
| Incandescent Equivalent : | 500W                        |
| HID Equivalent :          | 175W                        |
| Operating Temperature :   | -25C (-13F) to +45C (+113F) |
| Operating Position:       | Universal                   |
| Power Factor :            | >0.9                        |
| Light Source:             | LED                         |
| Voltage Type:             | AC Only; Range Voltage      |
| Warranty:                 | 5-Years                     |

#### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923131189       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 5.59 x 5.59 x 5.31 |

#### INFO

|                    |                                      |
|--------------------|--------------------------------------|
| Installation Note: | Not for use in vapor tight fixtures. |
|--------------------|--------------------------------------|

Project/Job Name:

Location:

Fixture Type:

Notes:

**S13118** - 60 Watt LED Utility Light 4000K; Medium base; Adjustable Beam Angle; 100-277 Volt



#### PHYSICAL

|                   |                       |
|-------------------|-----------------------|
| Base:             | Medium                |
| Shape:            | Corncob               |
| Finish:           | Clear                 |
| Lens Finish:      | Clear                 |
| Lens Material:    | Plastic (PS)          |
| Dimensions (In.): | MOL: 4.06 - MOD: 8.63 |
| Weight (Lbs.):    | 1.43                  |
| Material:         | Plastic               |
| Housing Color:    | White                 |
| Sensor:           | No Photocell          |

#### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| Indoor/Outoor:              | Indoor                            |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| NOM Certificate No.:        | NTEC21EN000585                    |
| NOM Expiration Date:        | 2/14/2022                         |
| Enclosure Rating:           | Open Rated Lamp                   |
| Rated For Enclosed Fixture: | No                                |
| FCC Compliant:              | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S13118** - 60 Watt LED Utility Light 4000K; Medium base;  
Adjustable Beam Angle; 100-277 Volt

## ACCESSORIES

---



**80-929** LED HID Surge Protector; 100-277V AC; 10KV Protection Level

---



**90-445** Medium baseGlazed Porcelain Ceiling Receptacle; Screw Terminals; 4-3/8" Diameter; 660W; 250V

---