



#### ELECTRICAL

Technology:	LED
Watts:	60W
Volts:	120V-277V
Lumens:	5880L
CRI:	80+
Rg Value :	8
CCT (Kelvins):	4000K - Cool White
Beam Spread :	120-270
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	500W
HID Equivalent :	175W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Operating Position:	Universal
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923131196
Each Quantity:	1
Each Dimensions:	5.60 x 5.60 x 5.51

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------

Project/Job Name:

Location:

Fixture Type:

Notes:

**S13119** - 60 Watt LED Motion Sensor Utility Light 4000K; Medium base; Adjustable Beam Angle; 100-277 Volt



#### PHYSICAL

Base:	Medium
Shape:	Corncob
Finish:	Clear
Lens Finish:	Clear
Lens Material:	Plastic (PS)
Dimensions (In.):	MOL: 4.33 - MOD: 8.63
Weight (Lbs.):	1.48
Material:	Die-Cast Aluminum
Housing Color:	White
Sensor:	Has Motion Sensor

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21EN000585
NOM Expiration Date:	2/14/2022
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



**S13119** - 60 Watt LED Motion Sensor Utility Light 4000K; Medium base; Adjustable Beam Angle; 100-277 Volt

## ACCESSORIES

---



**80-929** LED HID Surge Protector; 100-277V AC; 10KV Protection Level

---



**90-445** Medium baseGlazed Porcelain Ceiling Receptacle; Screw Terminals; 4-3/8" Diameter; 660W; 250V

---