



#### ELECTRICAL

Technology:	LED
Watts:	25W
Volts:	120V-277V
Lumens:	3000L/3375L/3250L
CRI:	80+
Rg Value :	13
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	280
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	200W
Fluorescent Equivalent :	65W
HID Equivalent :	100W-150W
Operating Temperature :	-22C (-30F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection:	Built-in surge protection - 1KV
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923131615
Each Quantity:	1
Each Dimensions:	2.99 x 2.99 x 5.70

#### INFO

Specification Note:	Lumen/Watt/CCT Ratio Chart in Documents.	
Installation Note:	Not for use in vapor tight fixtures.	
Min Compartment Size:	Length: 6 in. Width: 6 in. Height: 8.5 in.	

Project/Job Name:

Location:

Fixture Type:

Notes:

**S13161** - 25 Watt; A-Plus 23; LED; CCT Selectable 3K/4K/5K; Medium base; Type B; Ballast Bypass; 100-277 Volt; ColorQuick Technology

- CCT Selectable



#### PHYSICAL

Base:	Medium
Shape:	AP23
Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 5.12 - MOD: 2.83
Weight (Lbs.):	0.49
Material:	Aluminum
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
RoHS Compliant:	Yes
Restrictions:	No Restrictions