



ELECTRICAL

Technology:	LED
Watts:	45W/22W
Volts:	120V-277V
Lumens:	5850L/3060L
CRI:	80+
Rg Value :	15
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	280
Hours Rated:	50000
Dimming Type :	Step Dimming
Incandescent Equivalent :	300W
Fluorescent Equivalent :	100W
HID Equivalent :	150W-175W
Operating Temperature :	-22C (-30F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 3KV
THD:	15%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923131653
Each Quantity:	1
Each Dimensions:	4.65 x 4.65 x 9.25

INFO

Specification Note:	Lumen/Watt/CCT Ratio Chart in Documents.
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 6 in. Width: 6 in. Height: 8.5 in.

Project/Job Name:

Location:

Fixture Type:

Notes:

S13165 - 45 Watt; A-Plus 32; LED; CCT Selectable and Wattage Selectable; Extended Mogul base; Type B; Ballast Bypass; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable



PHYSICAL

Base:	Mogul Extended
Shape:	AP32
Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 7.32 - MOD: 3.9
Weight (Lbs.):	1.38
Material:	Aluminum
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-GNP8VX
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
RoHS Compliant:	Yes
Restrictions:	No Restrictions