



#### ELECTRICAL

Technology:	LED
Watts:	65W/32W
Volts:	120V-277V
Lumens:	8450L/4420L
CRI:	80+
Rg Value :	15
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	280
Hours Rated:	50000
Dimming Type :	Step Dimming
Incandescent Equivalent :	400W
Fluorescent Equivalent :	150W
HID Equivalent :	175W-250W
Operating Temperature :	-22C (-30F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4KV
THD:	15%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923131677
Each Quantity:	1
Each Dimensions:	5.31 x 5.31 x 9.41

#### INFO

Specification Note:	Lumen/Watt/CCT Ratio Chart in Documents.
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 8 in. Width: 8 in. Height: 11 in.

Project/Job Name:

Location:

Fixture Type:

Notes:

**S13167** - 65 Watt; A-Plus 37; LED; CCT Selectable and Wattage Selectable; Extended Mogul base; Type B; Ballast Bypass; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable



#### PHYSICAL

Base:	Mogul Extended
Shape:	AP37
Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 8.03 - MOD: 4.61
Weight (Lbs.):	2.08
Material:	Aluminum
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-6YKMLZ
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
RoHS Compliant:	Yes
Restrictions:	No Restrictions