



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S14984 - 8 Watt A19 LED; Ceramic Red; Medium base; 360 deg.
Beam Angle; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	8W
Volts:	120V
Rg Value :	0
Beam Spread :	360
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	60W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Candlepower :	8
Power Factor :	0.7
Light Source:	LED
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923149849
Each Quantity:	1
Each Dimensions:	2.68 x 2.68 x 4.84

INFO

Additional Info:	Solid State LED lighting
Installation Note:	Can be used outdoors only when in an enclosed fixture
ROI Category:	Screw

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Ceramic Red
Dimensions (In.):	MOL: 4.13 - MOD: 2.38
Weight (Lbs.):	1.13
Material:	Ceramic / Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	ANC2101J00000725
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S14984 - 8 Watt A19 LED; Ceramic Red; Medium base; 360 deg.
Beam Angle; 120 Volt

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Leviton	66ELV
LeGrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Lutron	DVCL-153P
Lutron	DVLV-600P
Lutron	DVRP-253P
Leviton	IPE04-1L
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	RRD-6CL
Satco	S11268
Satco	S11270
Lutron	SLV-600P
Eaton	TAL06P-C2