



ELECTRICAL

| | |
|--------------------------|--------------------------------------|
| Technology: | LED |
| Watts: | 11W |
| Volts: | 120V-277V |
| Lumens: | 1300L/1400L/1350L |
| CRI: | 80+ |
| CCT (Kelvins): | 30K/40K/65K - Soft White to Daylight |
| Beam Spread : | 180 |
| Hours Rated: | 50000 |
| Dimmable: | Non-Dimmable - |
| Fluorescent Equivalent : | 22W |
| Operating Temperature : | -20C (-4F) to +45C (+113F) |
| THD: | 25% |
| Light Source: | LED |
| Voltage Type: | AC Only; Range Voltage |
| Warranty: | 5-Years |

PACKAGING

| | |
|------------------|--------------------|
| Each UPC: | 045923165108 |
| Each Quantity: | 1 |
| Each Dimensions: | 8.46 x 1.38 x 8.46 |

INFO

| | |
|-----------------------|---|
| Specification Note: | Only compatible with Electronic ballasts when installed in Type A mode. See ballast compatibility list for details. Not for use on magnetic ballasts.; Inner Diameter: 5.71 in. |
| Installation Note: | Not for use in vapor tight fixtures. |
| Min Compartment Size: | Length 11.4 in. Width 11.4 in. Height: 3.5 in. |

Project/Job Name:

Location:

Fixture Type:

Notes:

S16510 - LED Circline; 11 Watt; T9; 3000K/4000K/6500K CCT

Selectable; G10q Base; 120-277 Volt

- CCT Selectable



PHYSICAL

| | |
|-------------------|----------------------|
| Base: | G10q (4-Pin) |
| Shape: | T9 |
| Finish: | Frost |
| Dimensions (In.): | MOL: 8.08 - MOD: 1.2 |
| Weight (Lbs.): | 0.37 |
| Material: | Polycarbonate (PC) |
| Housing Color: | Frost |

COMPLIANCE

| | |
|-----------------------------|---------------------|
| Safety Listing: | cETLus - Classified |
| Location Rating: | Damp |
| Indoor/Outoor: | Indoor |
| DLC Approved: | No |
| BAA Compliant: | No |
| Rated For Enclosed Fixture: | Yes |
| FCC Compliant: | Yes |
| RoHS Compliant: | Yes |
| Restrictions: | No Restrictions |



S16510 - LED Circline; 11 Watt; T9; 3000K/4000K/6500K CCT
Selectable; G10q Base; 120-277 Volt

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
