



ELECTRICAL

Technology:	LED
Watts:	16W
Volts:	120V-277V
Lumens:	1850L/2000L/1950L
CRI:	80+
CCT (Kelvins):	30K/40K/65K - Soft White to Daylight
Beam Spread :	180
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
THD:	25%
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923165115
Each Quantity:	1
Each Dimensions:	12.01 x 1.38 x 12.01

INFO

Specification Note:	Only compatible with Electronic ballasts when installed in Type A mode. See ballast compatibility list for details. Not for use on magnetic ballasts.; Inner Diameter: 9.45 in.
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length 14.1 in. Width 14.1 in. Height: 3.5 in.

Project/Job Name:

Location:

Fixture Type:

Notes:

S16511 - LED Circline; 16 Watt; T9; 3000K/4000K/6500K CCT Selectable; G10q Base; 120-277 Volt

- CCT Selectable



PHYSICAL

Base:	G10q (4-Pin)
Shape:	T9
Finish:	Frost
Dimensions (In.):	MOL: 11.82 - MOD: 1.2
Weight (Lbs.):	0.57
Material:	Polycarbonate (PC)
Housing Color:	Frost

COMPLIANCE

Safety Listing:	cETLus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S16511 - LED Circline; 16 Watt; T9; 3000K/4000K/6500K CCT
Selectable; G10q Base; 120-277 Volt

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
