



Project/Job Name:

Location:

Fixture Type:

Notes:

S18401 - 4.5 Watt LED PL 2-PIN; 3000K; 450 Lumens; G23 base; 50000 Average rated hours; 360 deg. Beam Angle; 120-277 Volt; Type B; Ballast Bypass



ELECTRICAL

Technology:	LED
Watts:	4.5W
Volts:	120V-277V
Lumens:	450L
CRI:	80+
CCT (Kelvins):	3000K - Warm White
Beam Spread :	360
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	5W/7W/9W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923184017
Each Quantity:	1
Each Dimensions:	1.00 x 1.50 x 6.88

PHYSICAL

Base:	G23 (2-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.54 - MOD: 1.28
Weight (Lbs.):	0.53
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cETLus - Classified
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21ENM000316
NOM Expiration Date:	1/24/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S18401 - 4.5 Watt LED PL 2-PIN; 3000K; 450 Lumens; G23 base; 50000 Average rated hours; 360 deg. Beam Angle; 120-277 Volt; Type B; Ballast Bypass

ACCESSORIES



S8000

5 Watt LED Emergency Driver; 120-277 Volts



S8002

10 Watt LED Emergency Driver; 120-277 Volt
