



ELECTRICAL

Technology:	LED
Watts:	13W
Volts:	120V-277V
Lumens:	1850L/1950L/1950L
CRI:	80+
CCT (Kelvins):	30K/40K/50K - Neutral White to Natural Light
Beam Spread :	160
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	50W
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C:	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923184123
Each Quantity:	1
Each Dimensions:	22.83 x 1.18 x 4.88

INFO

Additional Info:	Replaces FB34T12/U3
Installation Note:	Not for use in vapor tight fixtures.

Project/Job Name:

Location:

Fixture Type:

Notes:

S18412 - 13 Watt T8 U-BEND LED; 50000 Hours; Medium Bi Pin Base; CCT Selectable; Type B; White Finish; 120-277 Volt

- CCT Selectable



PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	White
Lens Finish:	Frost
Lens Material:	Plastic
Dimensions (In.):	MOL: 22.6 - MOD: 1
Nominal Length:	22.5
Weight (Lbs.):	0.63
Material:	Plastic
Leg Spacing:	3
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S18412 - 13 Watt T8 U-BEND LED; 50000 Hours; Medium Bi Pin Base; CCT Selectable; Type B; White Finish; 120-277 Volt

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
