



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____



S19946 - 11 Watt; 2 Foot; T5 LED; Miniature Bi Pin Base; 3500K;
Type A; 1350 Lumens



ELECTRICAL

Technology:	LED
Watts:	11W
Volts:	Ballast Dependent
Lumens:	1350L
CRI:	80+
CCT (Kelvins):	3500K - Neutral White
Beam Spread :	185
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Incandescent Equivalent :	50W
Fluorescent Equivalent :	24W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required, check compatibility
Lamp Ballast Type A/B/C :	Type A
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Warranty:	5-Years

PHYSICAL

Base:	Miniature Bi Pin
Shape:	T5
Finish:	White
Lens Material:	Glass
Dimensions (In.):	MOL: 22.5 - MOD: 0.63
Nominal Length:	24
Weight (Lbs.):	0.13
Material:	Aluminum / Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923199462
Each Quantity:	1
Each Dimensions:	22.17 x 0.65 x 0.65

INFO

Additional Info:	Light Emitting Area of 325 degrees; System Wattage (Type A) - 14W
Installation Note:	Not for use in vapor tight fixtures.