



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S21233** - 4.5 Watt G25 LED Filament; White; Medium base; 90 CRI; 5000K; 120 Volt



### ELECTRICAL

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Technology:               | LED                                                |
| Watts:                    | 4.5W                                               |
| Volts:                    | 120V                                               |
| Lumens:                   | 350L                                               |
| CRI:                      | 90+                                                |
| Rg Value :                | 71                                                 |
| CCT (Kelvins):            | 5000K - Natural Light                              |
| Beam Spread :             | 320                                                |
| Hours Rated:              | 15000                                              |
| Dimmable:                 | Yes-Dimmable - 120V only                           |
| Dimmable Down To %:       | 100 to 10 percent                                  |
| Dimming Type :            | Forward Phase or Reverse Phase or Phase Selectable |
| Incandescent Equivalent : | 40W                                                |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                         |
| Power Factor :            | 0.77                                               |
| Light Source:             | LED Filament                                       |
| Voltage Type:             | AC Only                                            |
| Warranty:                 | 2-Years                                            |

### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923205484       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 3.50 x 3.50 x 5.28 |

### PHYSICAL

|                   |                                |
|-------------------|--------------------------------|
| Base:             | Medium                         |
| Shape:            | G25                            |
| Finish:           | White                          |
| Dimensions (In.): | MOL: 4.45 - MOD: 3.15          |
| Weight (Lbs.):    | 0.088                          |
| Material:         | Glass / Nickel Plated Aluminum |
| Housing Color:    | None                           |

### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Wet                               |
| Indoor/Outdoor:             | Indoor; Outdoor                   |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| NSF Approved:               | No                                |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S21233** - 4.5 Watt G25 LED Filament; White; Medium base; 90 CRI; 5000K; 120 Volt

#### DIMMER COMPATIBILITY

|         |             |
|---------|-------------|
| Leviton | 6672        |
| Leviton | 6674        |
| Leviton | 66ELV       |
| Lutron  | AYCL-153P   |
| Lutron  | CTRP-253P   |
| Eaton   | DALo6P-C2   |
| Leviton | DDMX1       |
| Leviton | DG6HD       |
| Leviton | DH6HD       |
| Leviton | DL6HD       |
| Leviton | DSEo6-10Z   |
| Leviton | DSL06       |
| Leviton | DSL06-1LZ   |
| Leviton | DSM10       |
| Eaton   | DULO6P-C2   |
| Lutron  | DVCL-153P   |
| Lutron  | DVRP-253P   |
| Leviton | DW6HD       |
| Leviton | DZ6HD       |
| Leviton | IPE04-1L    |
| Leviton | IPL06       |
| Lutron  | LECL-153PH  |
| Lutron  | MA-PRO      |
| Lutron  | MACL-153M   |
| Lutron  | MSCL-OP153M |
| Lutron  | NTCL-250    |

|                |            |
|----------------|------------|
| <b>Lutron</b>  | NTRP-250   |
| <b>Lutron</b>  | PD-10WX    |
| <b>Lutron</b>  | PD-6WCL    |
| <b>Lutron</b>  | RCL-153PNL |
| <b>Eaton</b>   | RF9640-ND  |
| <b>Legrand</b> | RHCL450PTC |
| <b>Leviton</b> | RNL06-10Z  |
| <b>Lutron</b>  | RRD-6CL    |
| <b>Lutron</b>  | RRD-PRO    |
| <b>Satco</b>   | S11268     |
| <b>Eaton</b>   | SUF7       |
| <b>Eaton</b>   | TAL06P-C2  |
| <b>Leviton</b> | TSL06      |
| <b>Leviton</b> | TSM10      |
| <b>Eaton</b>   | VSUL06D    |