



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21246 - 6 Watt G25 LED Filament; Clear; Medium base; 90 CRI;
3000K; 120 Volt; 2 Pack



ELECTRICAL

Technology:	LED
Watts:	6W
Volts:	120V
Lumens:	500L
CRI:	90+
Rg Value :	55
CCT (Kelvins):	3000K - Soft White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	60W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.75
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923205613
Each Quantity:	1
Each Dimensions:	7.01 x 3.43 x 5.20

PHYSICAL

Base:	Medium
Shape:	G25
Finish:	Clear
Dimensions (In.):	MOL: 4.45 - MOD: 3.15
Weight (Lbs.):	0.09
Material:	Glass / Nickel Plated Aluminum
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S21246 - 6 Watt G25 LED Filament; Clear; Medium base; 90 CRI;
3000K; 120 Volt; 2 Pack

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Leviton	66ELV
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DALo6P-C2
Leviton	DDL06
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSEo6-10Z
Leviton	DSL06
Leviton	DSL06-1LZ
Leviton	DSM10
Eaton	DULo6P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	DZ6HD
Leviton	IPE04-1L
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M

Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX
Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Eaton	SAL06P
Eaton	TAL06P-C2
Leviton	TSL06
Leviton	TSM10
Eaton	VSUL06D