



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21252 - 6 Watt G40 LED Filament; Clear; Medium base; 90 CRI; 2700K; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	6W
Volts:	120V
Lumens:	500L
CRI:	90+
Rg Value :	57
CCT (Kelvins):	2700K - Warm White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	60W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.76
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923205675
Each Quantity:	1
Each Dimensions:	5.12 x 5.12 x 7.24

PHYSICAL

Base:	Medium
Shape:	G40
Finish:	Clear
Dimensions (In.):	MOL: 6.54 - MOD: 4.88
Weight (Lbs.):	0.21
Material:	Glass / Nickel Plated Aluminum
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

Leviton 6672

Leviton 6674

Leviton 66ELV

Satco 86/103

Legrand ADTP703TU

Lutron AYCL-153P

Lutron CTRP-253P

Eaton DAL06P-C2

Leviton DDMX1

Leviton DG6HD

Leviton DH6HD

Leviton DL6HD

Leviton DSE06-10Z

Leviton DSL06

Leviton DSL06-1LZ

Leviton DSM10

Eaton DUL06P-C2

Lutron DVCL-153P

Lutron DVRP-253P

Leviton DW6HD

Leviton DZ6HD

Leviton IPE04-1L

Leviton IPL06

Lutron LECL-153PH

Lutron MA-PRO

Lutron MACL-153M

Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX
Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Eaton	SAL06P
Eaton	SUF7
Eaton	TAL06P-C2
Leviton	TSL06
Leviton	TSM10
Eaton	VSUL06D