



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S21264** - 4 Watt B11 LED Filament; Clear; Candelabra base; 90 CRI; 2700K; 120 Volt



#### ELECTRICAL

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Technology:               | LED                                                |
| Watts:                    | 4W                                                 |
| Volts:                    | 120V                                               |
| Lumens:                   | 350L                                               |
| CRI:                      | 90+                                                |
| Rg Value :                | 53                                                 |
| CCT (Kelvins):            | 2700K - Warm White                                 |
| Beam Spread :             | 300                                                |
| Hours Rated:              | 15000                                              |
| Dimmable:                 | Yes-Dimmable - 120V only                           |
| Dimmable Down To %:       | 100 to 10 percent                                  |
| Dimming Type :            | Forward Phase or Reverse Phase or Phase Selectable |
| Incandescent Equivalent : | 40W                                                |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                         |
| Power Factor :            | 0.76                                               |
| Light Source:             | LED Filament                                       |
| Voltage Type:             | AC Only                                            |
| Warranty:                 | 2-Years                                            |

#### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923205798       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 1.65 x 1.65 x 4.13 |

#### PHYSICAL

|                   |                                |
|-------------------|--------------------------------|
| Base:             | Candelabra                     |
| Shape:            | B11                            |
| Finish:           | Clear                          |
| Dimensions (In.): | MOL: 3.97 - MOD: 1.38          |
| Weight (Lbs.):    | 0.04                           |
| Material:         | Glass / Nickel Plated Aluminum |
| Housing Color:    | None                           |

#### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Listed                    |
| Location Rating:            | Wet                               |
| Indoor/Outdoor:             | Indoor; Outdoor                   |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| NOM Certificate No.:        | NOM-030-ENER-2016INTEC22ENM004056 |
| NOM Expiration Date:        | 4/25/2024                         |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| NSF Approved:               | No                                |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S21264** - 4 Watt B11 LED Filament; Clear; Candelabra base; 90 CRI; 2700K; 120 Volt

#### DIMMER COMPATIBILITY

|         |             |
|---------|-------------|
| Leviton | 6672        |
| Leviton | 6674        |
| Satco   | 86/103      |
| Lutron  | AYCL-153P   |
| Lutron  | CTRP-253P   |
| Eaton   | DALo6P-C2   |
| Leviton | DDMX1       |
| Leviton | DG6HD       |
| Leviton | DH6HD       |
| Leviton | DL6HD       |
| Leviton | DSL06       |
| Leviton | DSL06-1LZ   |
| Leviton | DSM10       |
| Eaton   | DULO6P-C2   |
| Lutron  | DVCL-153P   |
| Lutron  | DVRP-253P   |
| Leviton | DW6HD       |
| Leviton | DZ6HD       |
| Leviton | IPL06       |
| Lutron  | LECL-153PH  |
| Lutron  | MA-PRO      |
| Lutron  | MACL-153M   |
| Lutron  | MSCL-OP153M |
| Lutron  | NTCL-250    |
| Lutron  | NTRP-250    |
| Lutron  | PD-10WX     |

|                |            |
|----------------|------------|
| <b>Lutron</b>  | PD-6WCL    |
| <b>Lutron</b>  | RCL-153PNL |
| <b>Eaton</b>   | RF9640-ND  |
| <b>Legrand</b> | RHCL450PTC |
| <b>Leviton</b> | RNL06-10Z  |
| <b>Lutron</b>  | RRD-6CL    |
| <b>Lutron</b>  | RRD-PRO    |
| <b>Satco</b>   | S11268     |
| <b>Eaton</b>   | SUF7       |
| <b>Leviton</b> | TSL06      |
| <b>Leviton</b> | TSM10      |
| <b>Eaton</b>   | VSUL06D    |