



#### ELECTRICAL

|                           |  |
|---------------------------|--|
| Technology:               | LED  |
| Watts:                    | 16W  |
| Volts:                    | 120V-277V  |
| Lumens:                   | 1850L  |
| CRI:                      | 80+  |
| CCT (Kelvins):            | 27K/30K/35K/40K/50K - Warm White to Natural Light    |
| Beam Spread :             | 120  |
| Hours Rated:              | 50000  |
| Fluorescent Equivalent :  | 42W  |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                           |
| Ballasting Requirements : | Ballast required (Type A) or Ballast Bypass (Type B) |
| Lamp Ballast Type A/B/C : | Type A/B   |
| Operating Position:       | Universal  |
| THD:                      | 20%  |
| Power Factor :            | 0.9  |
| Light Source:             | LED  |
| Voltage Type:             | AC Only; Range Voltage                               |
| Warranty:                 | 5-Years  |

#### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923211645       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 2.44 x 2.44 x 6.89 |

#### INFO

|                    |   |
|--------------------|---|
| Installation Note: | Suggested wattage equivalency = 42W CFL |
|--------------------|---|

Project/Job Name:

Location:

Fixture Type:

Notes:

**S21412** - 16 Watt PL 4-Pin LED; 1850 Lumens; G24q Base; CCT Selectable; White Finish; 120-277 Volts

- CCT Selectable



#### PHYSICAL

|                   |                               |
|-------------------|-------------------------------|
| Base:             | G24q-4 (4-Pin)                |
| Shape:            | PL                            |
| Finish:           | White                         |
| Dimensions (In.): | MOL: 6.76 - MOD: 2.36         |
| Weight (Lbs.):    | 0.4                           |
| Material:         | Aluminum / Polycarbonate (PC) |
| Housing Color:    | White                         |

#### COMPLIANCE

|                             |   |
|-----------------------------|---|
| Safety Listing:             | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating:            | Damp  |
| Indoor/Outoor:              | Indoor  |
| DLC Approved:               | No  |
| BAA Compliant:              | No  |
| Rated For Enclosed Fixture: | No  |
| FCC Compliant:              | Yes   |
| NSF Approved:               | Yes   |
| RoHS Compliant:             | Yes   |
| Restrictions:               | No Restrictions                                       |

**ACCESSORIES**

**80-973** Emergency Driver Enclosure; For use with S8000 and S8002



**80-987** Emergency Remote Test Switch; Single Gang Plate; White Finish



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt